

7526 So. State Street  
Midvale, Utah 84047




(801)563-9600  
(801)569-9606 Fax  
(800)657-6394

## Snow Tarp Specifications Sheet

|   |  |
|---|--|
| <b>Tarp Cut Size</b>  | 20' x 20'                              |
| <b>Webbing</b>  | 6000 lb. rating                        |
| <b>Fabric Type</b>  | PVC Coated Polyester ( Woven )         |
| <b>Weight</b><br>( FS-191-5041 )  | 18.5 oz / yard <sup>2</sup>            |
| <b>Thread Count</b> ( Warp x Fill )   | 18 x 17 ( 1000D x 1300D )              |
| <b>Tensile Strength, Grab Method</b> ( lbs. )<br>( FS-191-5100 )              | Warp 410 x Fill 410                    |
| <b>Tensile Strength, Strip Method</b> ( lbs. )<br>( FS-191-5102 )             | Warp 300 x Fill 300                    |
| <b>Tear Strength, Tongue Method</b> ( lbs. )<br>( FS-191-5134 )               | Warp 100 x Fill 100                    |
| <b>Adhesion</b> ( lbs. / inch )<br>( FS-191-5970 )                            | Warp 12 X Fill 10                      |
| <b>Abrasion Resistance</b><br>( FS-191-5306 )                                 | 400 Cycles                             |
| <b>Hydrostatic Resistance</b> ( lbs. / inch <sup>2</sup> )<br>( FS-191-5512 ) | At least 600 PSI                       |
| <b>Cold Crack</b><br>( FS-191-5874 )  | -40° F                                 |
| <b>U.V. Resistance</b><br>( Weather-O-Meter )                                 | No Excessive Fading<br>After 300 Hours |
| <b>High Temperature Resistance</b><br>( FS-191-5072 )                         | 180° F ( Does Not Block )              |

# **RATED 3000 lbs. MAX.**

- ⚠ **FOR USE WITH NEWLY FALLEN SNOW ONLY**
- ⚠ **NEVER USE A TARP WITH HOLES OR TEARS**
- ⚠ **NEVER USE TO LIFT EQUIPMENT OR SUPPLIES**
- ⚠ **WEBBING MUST ALWAYS BE FACING DOWN**



## **NEVER STAND UNDER LOAD**

